

LOTBLOCKS™

PARKING STOPS

RECYCLED PLASTIC PARKING STOPS

Replace unsightly, old, concrete parking stops with 100% recycled plastic LotBlocks™ Parking Stops. They will not chip or crack like concrete and resist attack from gas, oil, salt, sunlight and chemicals. LotBlocks™ are molded in solid colors and never need painting. They are light enough to ship via UPS and can easily be installed by one person.

4 FOOT CAR PARKING STOP SPECIFICATIONS

MODEL W/ HARDWARE	MODEL W/O HARDWARE	DESCRIPTION	A LENGTH	B HEIGHT	C WIDTH	WEIGHT
CS4S-H	CS4S	Standard 4 ft. Car Parking Stop	48 in. (1219 mm)	4 in. (102 mm)	6 in. (152 mm)	20 lbs. (9.1 kg)
CS4D-H	CS4D	Deluxe 4 ft. Car Parking Stop	48 in. (1219 mm)	4.5 in. (115 mm)	7 in. (179 mm)	24 lbs. (10.9 kg)

Specify color after model No: Y = Yellow; G = Gray; B = Blue

6 FOOT CAR PARKING STOP SPECIFICATIONS

MODEL W/ HARDWARE	MODEL W/O HARDWARE	DESCRIPTION	A LENGTH	B HEIGHT	C WIDTH	WEIGHT
CS6C-H	CS6C	Compact 6 ft. Car Parking Stop	72 in. (1829 mm)	3.25 in. (83 mm)	6 in. (152 mm)	25 lbs. (11.4 kg)
CS6S-H	CS6S	Standard 6 ft. Car Parking Stop	72 in. (1829 mm)	4 in. (102 mm)	6 in. (152 mm)	30 lbs. (13.6 kg)
CS6D-H	CS6D	Deluxe 6 ft. Car Parking Stop	72 in. (1829 mm)	4.5 in. (115 mm)	7 in. (179 mm)	36 lbs. (16.4 kg)


Specify color after model No: Y = Yellow; G = Gray; B = Blue

8 FOOT TRUCK PARKING STOP SPECIFICATIONS

MODEL W/ HARDWARE	MODEL W/O HARDWARE	DESCRIPTION	A LENGTH	B HEIGHT	C WIDTH	WEIGHT
TS8-H	TS8	8 ft. Truck Parking Stop	96 in. (2448 mm)	7 in. (179 mm)	10 in. (255 mm)	100 lbs. (45.5 kg)

Specify color after model No: Y = Yellow; G = Gray; B = Blue

- Solid Plastic
- Easy Installation
- Maintenance Free
- Lightweight - Yet Stable
- Chemical and Weather Resistant
- 100% Recycled Material



NOTE: One set of Mounting Hardware is included at no additional charge with each LotBlock Parking Stop purchased. Please specify type of hardware desired based on installation to either concrete or asphalt.

MOUNTING HARDWARE SELECTION GUIDE

HARDWARE PACKAGE (choose one)	APPLICATION	PRODUCT	Lag Screws (0.5 x 8 in. Car Stops) (0.5 x 10 in. Truck Stops)	Expanding Lag Shields	Flat Washers (0.5 in.)	Steel Spikes (0.5 x 12 in. w/ 1.125 Head)
Lag Bolt Hardware	Recommended for concrete where drilling holes is permitted.	4' Car Stop	2	2	4	—
		6' Car Stop	3	3	6	—
		8' Truck Stop	4	4	8	—
Steel Spike Hardware	Recommended for asphalt surfaces.	4' Car Stop	—	—	—	2
		6' Car Stop	—	—	—	3
		8' Truck Stop	—	—	—	4

NOTE: Please make your product selection carefully. Parking Stops are non-returnable.

SlowMo™

SPEED BUMPS

Alert drivers to potentially hazardous driveways and parking areas with 100% recycled plastic SlowMo™ Speed Bumps. They help prevent accidents due to excessive speed. SlowMo™ Speed Bumps will not chip or crack under heavy loads and resist attack from gas, oil, salt, sunlight and chemicals. Molded in solid colors, SlowMos never need painting. They can be anchored end-to-end for longer lengths. SlowMo™ Speed bumps are light enough to ship via UPS and can easily be installed by one person.

4 FOOT SPEED BUMP SPECIFICATIONS

MODEL W/ HARDWARE	MODEL W/O HARDWARE	DESCRIPTION	A LENGTH	B HEIGHT	C WIDTH	WEIGHT
SB4S-H	SB4S	Standard 4 ft. Speed Bump	48 in. (1219 mm)	2 in. (51 mm)	10 in. (255 mm)	22 lbs. (10 kg)
SB4D-H	SB4D	Deluxe 4 ft. Speed Bump	48 in. (1219 mm)	2.25 in. (58 mm)	12 in. (306 mm)	28 lbs. (12.7 kg)

Color - Yellow

6 FOOT SPEED BUMP SPECIFICATIONS

MODEL W/ HARDWARE	MODEL W/O HARDWARE	DESCRIPTION	A LENGTH	B HEIGHT	C WIDTH	WEIGHT
SB6S-H	SB6S	Standard 6 ft. Speed Bump	72 in. (1836 mm)	2 in. (51 mm)	10 in. (255 mm)	25 lbs. (11.4 kg)
SB6D-H	SB6D	Deluxe 6 ft. Speed Bump	72 in. (1836 mm)	2.25 in. (58 mm)	12 in. (306 mm)	41 lbs. (18.6 kg)


Color - Yellow

9 FOOT SPEED BUMP SPECIFICATIONS

MODEL W/ HARDWARE	MODEL W/O HARDWARE	DESCRIPTION	A LENGTH	B HEIGHT	C WIDTH	WEIGHT
SB9S-H	SB9S	Standard 9 ft. Speed Bump	108 in. (2754 mm)	2 in. (51 mm)	10 in. (255 mm)	50 lbs. (22.7 kg)

Color - Yellow

- Solid Plastic
- Easy Installation
- Maintenance Free
- Lightweight - Yet Stable
- Chemical and Weather Resistant
- 100% Recycled Material



NOTE: One set of Mounting Hardware is included at no additional charge with each SlowMo Speed Bump purchased. Please specify type of hardware desired based on installation to either concrete or asphalt.

MOUNTING HARDWARE SELECTION GUIDE

HARDWARE PACKAGE (choose one)	APPLICATION	PRODUCT	Lag Screws (0.5 x 5.5 in.)	Expanding Lag Shields	Flat Washers (0.5 in.)	Steel Spikes (0.5 x 12 in. w/ 1.125 Head)
Lag Bolt Hardware	Recommended for concrete where drilling holes is permitted.	4' Speed Bump	3	3	6	—
		6' Speed Bump	4	4	8	—
		9' Speed Bump	5	5	10	—
Steel Spike Hardware	Recommended for asphalt surfaces.	4' Speed Bump	—	—	—	3
		6' Speed Bump	—	—	—	4
		9' Speed Bump	—	—	—	5

NOTE: Please make your product selection carefully. Speed Bumps are non-returnable.